



(12) **United States Patent**  
**Tatcho et al.**

(10) **Patent No.:** **US 9,411,006 B1**  
(45) **Date of Patent:** **\*Aug. 9, 2016**

(54) **METHOD OF LOCATING A FAULT IN A POWER DISTRIBUTION SYSTEM COMPRISING AT LEAST ONE MICROTURBINE DISTRIBUTED RESOURCE**

2001/002 (2013.01); H02J 2001/004 (2013.01);  
H02J 2001/006 (2013.01); H02J 2001/008 (2013.01)

(71) Applicant: **The Florida State University Research Foundation, Inc.**, Tallahassee, FL (US)

(72) Inventors: **Passinam Tatcho**, Tallahassee, FL (US);  
**Mischa Steurer**, Crawfordville, FL (US); **Hui Li**, Tallahassee, FL (US)

(73) Assignee: **The Florida State University Research Foundation, Inc.**, Tallahassee, FL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/962,434**

(22) Filed: **Dec. 8, 2015**

#### Related U.S. Application Data

(63) Continuation of application No. 14/166,467, filed on Jan. 28, 2014, now Pat. No. 9,274,161.

(60) Provisional application No. 61/757,507, filed on Jan. 28, 2013.

(51) **Int. Cl.**  
**G01R 31/14** (2006.01)  
**G01R 31/08** (2006.01)  
**G01R 31/00** (2006.01)  
**H02J 1/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G01R 31/086** (2013.01); **H02J 1/00** (2013.01); **G01R 31/00** (2013.01); **G01R 31/08** (2013.01); **G01R 31/088** (2013.01); **H02J**

#### (58) Field of Classification Search

CPC .... G01R 31/086; G01R 31/088; G01R 31/00;  
G01R 31/08; H02J 1/00; H02J 2001/002;  
H02J 2001/004; H02J 2001/0006; H02J  
2001/008

USPC ..... 324/523, 509, 522  
See application file for complete search history.

#### (56) References Cited

##### U.S. PATENT DOCUMENTS

2010/0102824 A1 4/2010 Tremblay et al.  
2012/0091817 A1 4/2012 Seymour et al.  
2012/0271470 A1 10/2012 Flynn et al.

##### OTHER PUBLICATIONS

Tatcho et al. "A Real Time Digital Test bed for a Smart Grid using RTDS", IEEE International Symposium on Power Electronics for Distributed Generation Systems, pp. 658-661, 2010.\*

(Continued)

*Primary Examiner* — Farhana Hoque

(74) *Attorney, Agent, or Firm* — Molly L. Sauter; Smith & Hopen, P.A.

#### (57) ABSTRACT

The present invention provides a method to ensure that distributed resources of a power distribution system remain connected to the circuitry of the power distribution system when a fault occurs at a distributed resource node to assist in identifying the location of the fault by continuing to inject current from the distributed resources into the distribution system, wherein at least one of the distributed resources is a micro-turbine.

**5 Claims, 5 Drawing Sheets**

